










Maße für Schrauben

Außensechskantschrauben

DIN	Maße	M 6	M 8	M 10	M 12	M 16	M 20	M 24	M 30	M 36	M 42	M 48	M 56	
561-A		k	5	6	7	9	11	14	17	21	25	30	34	40
		s	8	10	13	16	18	24	30	36	46	55	65	75
561-B		a (Form B)	2,5	3	4	4	4,5	6	7	7,5	9	10	12	12
		z ₂	3	4	5	6	8	10	12	15	18	21	24	28
561-B		d _p	4	5,5	7	8,5	12	15	18	23	28	32	38	45


DIN	Maße	M 8	M 10	M 12	M 14	M 16	M 18	M 20	M 24	M 30	
609 610		k	5,3	6,4	7,5	8,8	10	11,5	12,5	15	19
		s	13	16	18	21	24	27	30	36	46
		d _s [*]	9	11	13	15	17	19	21	25	32
		b ₁	14,5	17,5	20,5	22	25	27,5	28,5	-	-
		b ₂	16,5	19,5	22,5	24	27	29,5	30,5	36,5	43
		b ₃	21,5	24,5	27,5	29	32	34,5	35,5	41,5	48

b₁) Für l ≤ 50 mm
b₂) Für 50 mm < l ≤ 150 mm
b₃) Für l > 150 mm
*) Passschafftol. k6 für Bohrungstol. H7



DIN	Maße	M 5	M 6	M 8	M 10	M 12	M 16	
6921		k	5,4	6,6	8,1	9,2	11,5	14,4
		s	8	10	13	15	16	21
		d _c	11,58	14,2	18	22,3	26,6	35
		b ₁	16	18	22	26	30	38
		b ₂	-	-	28	32	36	44
		b ₃	-	-	-	-	-	57

b₁) Für l ≤ 125 mm
b₂) Für 125 mm < l ≤ 200 mm
b₃) Für l > 200 mm

Stiftschrauben

DIN	Maße	M 6	M 8	M 10	M 12	M 16	M 20	
835		b ₁	12	16	20	24	32	40
		x ₁	2,5	3,2	3,8	4,3	5,0	6,3
		b ₂ ¹⁾	18	22	26	30	38	46
		b ₂ ²⁾	24	28	32	36	44	52
		b ₂ ³⁾	-	-	45	49	57	65

1) b₁) Für l ≤ 125 mm
2) b₂) Für 125 mm < l ≤ 200 mm
3) b₂) Für l > 200 mm

DIN	Maße	M 5	M 6	M 8	M 10	M 12	M 14	M 16	M 18	
938		b ₁ (DIN 938)	5	6	8	10	12	14	16	18
		b ₁ (DIN 939)	6,5	7,5	10	12	15	18	20	22
		x ₁	2	2,5	3,2	3,8	4,3	5	5	6,3
		x ₂	1	1,25	1,6	1,9	2,2	2,5	2,5	3,2
		b ₂ ¹⁾	16	18	22	26	30	34	38	42
		b ₂ ²⁾	22	24	28	32	36	40	44	48
		b ₂ ³⁾	-	-	-	45	49	53	57	61
939		b ₁ (DIN 938)	20	22	24	27	30	33	36	
		b ₁ (DIN 939)	25	28	30	35	38	42	45	
		x ₁	6,3	6,3	7,5	7,5	9	9	10	
		x ₂	3,2	3,2	3,8	3,8	4,5	4,5	5	
		b ₂ ¹⁾	46	50	54	60	66	72	78	
		b ₂ ²⁾	53	56	60	66	72	78	84	
		b ₂ ³⁾	65	69	73	79	85	91	97	

b₁ = Einschraubende
b₂ = Mutternende
1) b₁) Für l ≤ 125 mm
2) b₂) Für 125 mm < l ≤ 200 mm
3) b₂) Für l > 200 mm