

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LEDVANCE

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC35320

**Type of light source:**

|   |        |                                 |      |
|---|--------|---------------------------------|------|
| Lighting technology used:                           | other  | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | GY6.35 |                                 |      |
| Mains or non-mains:                                 | NMLS   | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No     | Envelope:                       | -    |
| High luminance light source:                        | No     |                                 |      |
| Anti-glare shield:                                  | No     | Dimmable:                       | Yes  |

## Product parameters

| Parameter  | Value                | Parameter  | Value                  |
|--|----------------------|--|------------------------|
| <b>General product parameters:</b>   |                      |  |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 25                   | Energy efficiency class  | G                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 440 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 800                  |
| On-mode power ( $P_{on}$ ), expressed in W   | 25,0                 | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                    | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 100                    |
| Outer dimensions without   | Height               | Spectral power distribution in the   | See image in last page |
|  | Width                |  |                        |
|  | Depth                |  |                        |

|   |   |  |                                      |       |
|---|---|--|--------------------------------------|-------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |   |  | range 250 nm to 800 nm, at full-load |       |
| Claim of equivalent power <sup>(a)</sup>  | - |  | If yes, equivalent power (W)         | -     |
|   |   |  | Chromaticity coordinates (x and y)   | 0,452 |

(a) - : not applicable;

(b) - : not applicable;

