## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: OSRAM

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

## Model identifier: AC34256

## Type of light source:

| Lighting technology used:     | CFLni   | Non-directional or directional: | NDLS |  |  |
|-------------------------------|---------|---------------------------------|------|--|--|
| Light source cap-type         | GX24q-4 |                                 |      |  |  |
| (or other electric interface) |         |                                 |      |  |  |
| Mains or non-mains:           | NMLS    | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No      | Envelope:                       | -    |  |  |
| High luminance light source:  | No      |                                 |      |  |  |
| Anti-glare shield:            | No      | Dimmable:                       | Yes  |  |  |
| Product parameters            |         |                                 |      |  |  |

| Parameter                            |  | Value                     | Parameter   | Value        |  |
|--------------------------------------|--|---------------------------|---|--------------|--|
| General product parameters:          |  |                           |   |              |  |
| • ·                                  | mption in on-<br>100 h), rounded<br>st integer                             | 44                        | Energy efficiency<br>class  | G            |  |
| indicating if it r<br>in a sphere (3 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 3 050 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 4 000        |  |
| On-mode p<br>expressed in W          | oower (P <sub>on</sub> ),  | 43,4                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |
| for CLS, expre                       | idby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal          | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |
| Outer<br>dimensions<br>without       | Height   | 165                       | Spectral power  | See image    |  |
|                                      | Width  | 12                        | distribution in the   | in last page |  |
|                                      | Depth  | 12                        | 1   | Page 1/3     |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|--|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)          | -     |
|  | Chromaticity<br>coordinates (x and y)   | 0,380 |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

