Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: MEGAM.	ΑN
--	----

Supplier's address: IDV GmbH MEGAMAN-Confirmation-Management, Birkenweiherstraße 2,

63505 Langenselbold, DE

Mode	l ide	ntifier:	MM21039
------	-------	----------	---------

_	•			
Type	Λt	light	COLL	rca.
IVDE	VI.	HEILL	SOUI	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Yes

Product parameters

Froduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	2	Energy efficiency class	G
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 800
On-mode pexpressed in W	oower (P _{on}),	2,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	<u>-</u>
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	57	Spectral power	See image
dimensions	Width	26	distribution in the	in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	26	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)		Ja	If yes, equivalent power (W)	11
			Chromaticity coordinates (x and y)	- -
Parameters for	LED and OLED lig	ht sources:		
R9 colour rendering index value - Survival factor		Survival factor	0,50	
the lumen maintenance factor		0,70		
Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	-	Colour consistency in McAdam ellipses	6
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (F	Pst LM)	-	Stroboscopic effect metric (SVM)	-

(a)'-': not applicable; (b)'-': not applicable;