## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: MAUL	
-------------------------------------	--

Supplier's address: Jakob Maul GmbH, Jakob-Maul-Str. 17 D-64732 Bad König

Model identifier: 8205009.200

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

without

Depth

. 7   0   1   1   1   1   1				
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap	o-type	Leiterplatten		
(or other electric interface)		Anschlussklemmen		
Mains or non-m	ains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	High luminance light source:			
Anti-glare shield	l:	No	Dimmable:	Yes
		Product paran	neters	I
Parameter		Value	Parameter	Value
		General product pa	arameters:	
~ .	nption in on- 00 h), rounded st integer	6	Energy efficiency class	F
indicating if it ro in a sphere (30	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	618 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500
On-mode pexpressed in W	oower (P <sub>on</sub> ),	5,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84
Outer	Height	77	Spectral power	See image
dimensions	Width	76	distribution in the	in last page
i+b.o.u+		<del> </del>		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	49			
		Chromaticity	0,434			
		coordinates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value 13		Survival factor	1,00			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;

