

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Gnosjö Konstsmide AB

**Supplier's address:** -

**Model identifier:** 6367-820

**Type of light source:**

|                                                     |      |                                 |      |
|-----------------------------------------------------|------|---------------------------------|------|
| Lighting technology used:                           | LED  | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | -    |                                 |      |
| Mains or non-mains:                                 | MLS  | Connected light source (CLS):   | Nein |
| Colour-tuneable light source:                       | Nein | Envelope:                       | -    |
| High luminance light source:                        | Nein |                                 |      |
| Anti-glare shield:                                  | Nein | Dimmable:                       | No   |

## Product parameters

| Parameter                                                                                                                                             | Value   | Parameter                                                                                                                                                  | Value                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                                    |         |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                         | 5       | Energy efficiency class                                                                                                                                    | G                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 83 in - | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | -                      |
| On-mode power ( $P_{\text{on}}$ ), expressed in W                                                                                                     | 3,6     | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal                                                                        | 0,30                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | ---                    |
| Outer dimensions without                                                                                                                              | Height  | Spectral power distribution in the                                                                                                                         | See image in last page |
|                                                                                                                                                       | Width   |                                                                                                                                                            |                        |
|                                                                                                                                                       | Depth   |                                                                                                                                                            |                        |

|                                                                                                                         |      |  |                                       |        |
|-------------------------------------------------------------------------------------------------------------------------|------|--|---------------------------------------|--------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |      |  | range 250 nm to 800 nm, at full-load  |        |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -    |  | If yes, equivalent power (W)          | -      |
|                                                                                                                         |      |  | Chromaticity coordinates (x and y)    | -<br>- |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |  |                                       |        |
| R9 colour rendering index value                                                                                         | -    |  | Survival factor                       | -      |
| the lumen maintenance factor                                                                                            | -    |  |                                       |        |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |  |                                       |        |
| displacement factor (cos $\phi_1$ )                                                                                     | -    |  | Colour consistency in McAdam ellipses | -      |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) |  | If yes then replacement claim (W)     | -      |
| Flicker metric (Pst LM)                                                                                                 | -    |  | Stroboscopic effect metric (SVM)      | -      |

(a) : not applicable;

(b) : not applicable;