## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LUTEC
--------------------------------	-------

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Type of light sour	Type	of li	ght	sourc	e:
--------------------	------	-------	-----	-------	----

Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light	Yes
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
		_	

## **Product parameters**

Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 100 h), rounded st integer	18	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode prespressed in W	oower (P <sub>on</sub> ),	17,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	2	Spectral power	See image
dimensions	Width	227	distribution in the	in last page
without	Depth	33		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity	0,463
		coordinates (x and y)	0,420
Parameters for LED and OLED lig	ght sources:		
R9 colour rendering index value	8	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

