Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: MEGAMAN

Supplier's address: IDV GmbH MEGAMAN-Confirmation-Management, Birkenweiherstraße 2,

63505 Langenselbold, DE

Model identifier: MM59304

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	3 Uui C	c.

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	-				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers		
Due de la transportante					

Product parameters

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	17	Energy efficiency class	G			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P _{on}), expressed in W	17,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	<u>-</u>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	85			

Outer	Height	50	Spectral power	See image	
dimensions	Width	34	distribution in the	in last page	
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	34	range 250 nm to 800 nm, at full-load		
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-	
			Chromaticity	0,380	
			coordinates (x and y)	0,380	
Parameters for LED and OLED light sources:					
R9 colour rendering index value		0	Survival factor	0,50	
the lumen maintenance factor		0,70			

(a)'-': not applicable;

(b)'-': not applicable;

