

# Switch - FL SWITCH SF 7TX/FX - 2832726

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ethernet Switch, 7 TP RJ45 ports, 1 FO port, 100 Mbps full duplex in SC-D format, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function

## Product Features

- Auto negotiation and autocrossing detection simplifies installation and setup
- Security options with cable locking
- Relay contact for alarm processing of voltage states
- Local diagnostic indicators with LEDs
- RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps

## Ethernet

### Key commercial data

package_quantity	1
GTIN	4017918952228

## Technical data

### Dimensions

Width	135 mm
Height	115.3 mm
Depth	30 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	5 % ... 95 % (no condensation)
Air pressure (operation)	86 kPa ... 108 kPa (up to 1500 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above mean sea level)
Noise immunity	EN 61000-6-2:2005

### Interfaces

Interface 1	Ethernet (RJ45)
No. of ports	7 (RJ45 ports)
Connection method	RJ45
Note on connection method	Auto negotiation and autocrossing

# Switch - FL SWITCH SF 7TX/FX - 2832726

## Technical data

### Interfaces

<b>Transmission physics</b>	Ethernet in RJ45 twisted pair
<b>Transmission speed</b>	10/100 MBit/s
<b>Transmission length</b>	100 m (per segment)
<b>Signal LEDs</b>	Data receive, link status
<b>Interface 2</b>	Fiber optic interface
<b>No. of ports</b>	1 (FO port)
<b>Connection method</b>	SC
<b>Transmission physics</b>	Multimode fiberglass
<b>Transmission speed</b>	100 MBit/s (SC-D, full duplex)
<b>Transmission length</b>	6400 m (fiberglass with F-G 50/125 0.7 dB/km F1200)
<b>Wavelength</b>	1300 nm
<b>Interface 4</b>	Potential-free signaling contact
<b>Connection method</b>	Plug-in/screw connection via COMBICON

### Function

<b>Basic functions</b>	Unmanaged switch / autonegotiation, complies with IEEE 802.3, store and forward switching mode
<b>Status and diagnostic indicators</b>	LEDs: U <sub>S1</sub> , U <sub>S2</sub> (redundant voltage supply), link and activity per port

### Network expansion parameters

<b>Cascading depth</b>	Network, linear, and star structure: any
<b>Maximum conductor length ((twisted pair)</b>	100 m

### Supply voltage

<b>Supply voltage</b>	24 V DC
<b>Residual ripple</b>	3.6 V <sub>PP</sub> (within the permitted voltage range)
<b>Supply voltage range</b>	18.5 V DC ... 30.2 V DC
<b>Typical current consumption</b>	typ. 220 mA
<b>Max. current consumption</b>	typ.

### General

<b>Mounting type</b>	DIN rail
<b>Type AX</b>	Block design
<b>Weight</b>	260 g
<b>Housing material</b>	Aluminum
<b>Noise emission</b>	EN 61000-6-4

### Conformity with EMC directives

<b>Developed in acc. with standard</b>	IEC 61000-6.2
<b>Test standard</b>	IEC 61000-4-2 (ESD)
<b>Test result</b>	Criterion B
<b>Test standard</b>	IEC 61000-4-3 (immunity to radiated interference)
<b>Test result</b>	Criterion A
<b>Test standard</b>	IEC 61000-4-4 (burst)

# Switch - FL SWITCH SF 7TX/FX - 2832726

## Technical data

### Conformity with EMC directives

<b>Test result</b>	Criterion A
<b>Test standard</b>	IEC 61000-4-5 (surge)
<b>Test result</b>	Criterion A
<b>Test standard</b>	IEC 61000-4-6 (immunity to conducted interference)
<b>Test result</b>	Criterion A
<b>Test standard</b>	IEC 61000-4-8 (immunity to magnetic fields)
<b>Test result</b>	Criterion A
<b>Test standard</b>	EN 55022 (emitted interference)
<b>Test result</b>	Criterion A

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27250501
<b>eCl@ss 4.1</b>	27250501
<b>eCl@ss 5.0</b>	27250501
<b>eCl@ss 5.1</b>	27250501
<b>eCl@ss 6.0</b>	19170106
<b>eCl@ss 7.0</b>	19170106
<b>eCl@ss 8.0</b>	19170106

### ETIM

<b>ETIM 2.0</b>	EC000734
<b>ETIM 3.0</b>	EC000734
<b>ETIM 4.0</b>	EC000734
<b>ETIM 5.0</b>	EC000734


### UNSPSC

<b>UNSPSC 6.01</b>	43172015
<b>UNSPSC 7.0901</b>	43201404
<b>UNSPSC 11</b>	43172015
<b>UNSPSC 12.01</b>	43201410
<b>UNSPSC 13.2</b>	43201410

## approvals




UL Listed / cUL Listed / cULus Listed / UL Listed / cUL Listed / cULus Listed /

### Approval details


---

# Switch - FL SWITCH SF 7TX/FX - 2832726

approvals



accessories

## Connector set

FL PLUG RJ45 GR/2 - 2744856



FL PLUG RJ45 GN/2 - 2744571



## Data cable by the meter

## Switch - FL SWITCH SF 7TX/FX - 2832726

### accessories

FL CAT5 HEAVY - 2744814



FL CAT5 FLEX - 2744830



### Universal tools

FL CRIMPTOOL - 2744869



### Patch cable

FL CAT5 PATCH 0,3 - 2832250



FL CAT5 PATCH 0,5 - 2832263



## Switch - FL SWITCH SF 7TX/FX - 2832726

### accessories

FL CAT5 PATCH 1,0 - 2832276



FL CAT5 PATCH 1,5 - 2832221



FL CAT5 PATCH 2,0 - 2832289



FL CAT5 PATCH 3,0 - 2832292



FL CAT5 PATCH 5,0 - 2832580



FL CAT5 PATCH 7,5 - 2832616



## Switch - FL SWITCH SF 7TX/FX - 2832726

### accessories

---

FL CAT5 PATCH 10,0 - 2832629



### Protective cap

FL RJ45 PROTECT CAP - 2832991



### End block

E/NS 35 N - 0800886



### Drawings

© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>