

VG K (standard plastic cable gland)
VG M16-K67 5-10

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Cable glands for professional use in industrial applications which meet the highest demands in terms of quality and safety. They are available made from polyamide, polystyrene and brass.

General ordering data

Type	VG M16-K67 5-10
Order No.	1909680000
Version	VG K (standard plastic cable gland), Cable glands, M 16, 10 mm, OD min. 5 - OD max. 10 mm, Polyamide 6
GTIN (EAN)	4032248536603
Qty.	50 pc(s).

**VG K (standard plastic cable gland)
VG M16-K67 5-10**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Length	40 mm	Length (inches)	1.575 inch
Net weight	9.08 g		

General information

AF size 1	22 mm	Cable glands	metric
External thread	M 16	Length of thread	10 mm
Material	Polyamide 6	Operating temperature range, max.	100 °C
Operating temperature range, min.	-20 °C	Outer cable diameter, max.	10 mm
Outer cable diameter, min.	5 mm	Pitch of thread	1.5 mm
Protection degree	IP67	Seal insert	NBR
Standards	DIN EN 62444, EN 62444, IEC 62444	Torque for cap nut, max.	3.5 Nm
Torque for cap nut, min.	2.5 Nm	Torque for connecting adapter, max.	4.75 Nm
Torque for connecting adapter, min.	3.75 Nm	Torque for lock nut, max.	4.75 Nm
Torque for lock nut, min.	3.75 Nm	UL 94 flammability rating	V-2

Classifications

ETIM 3.0	EC000441	ETIM 4.0	EC000441
ETIM 5.0	EC000441	ETIM 6.0	EC000441
UNSPSC	30-21-18-01	eClass 5.1	27-14-91-09
eClass 6.2	27-14-91-09	eClass 7.1	27-14-91-09
eClass 8.1	27-14-91-09	eClass 9.0	27-14-44-32
eClass 9.1	27-14-44-32		

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP