

Jumper - BRIDGE- 6 - 2900750

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



3-phase loop bridge for 6 modules of the CONTACTRON family with 22.5 mm housing width.

Figure shows variant for 4 modules

Product Features

- Suitable for CONTACTRON series ELR H3, ELR H5, ELR (W)3, EMM...IFS
- Bridging of 2 to 10 devices with maximum module spacing of 22.5 mm
- Considerable reduction in wiring
- Up to 575 V AC/3 x 25 A

Key commercial data

package_quantity	1
GTIN	4046356528269

Technical data

Dimensions

Length of the connecting cable	0.3 m
--------------------------------	-------

General

Nominal voltage U_N	575 V AC
Nominal current I_N	25 A
Number of bridgeable modules	6

classifications

eCl@ss

eCl@ss 4.0	27371190
eCl@ss 4.1	27371190
eCl@ss 5.0	27371692
eCl@ss 5.1	27371692
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140

Jumper - BRIDGE- 6 - 2900750

classifications

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121402
UNSPSC 12.01	39121402
UNSPSC 13.2	39121402

Drawings

Application drawing

