


# PCB terminal block - FFKDSA1/V-2,54- 4 - 1789595

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



PCB terminal block, Nominal current: 6 A, Nom. voltage: 160 V, Pitch: 2.54 mm, Number of positions: 4, Connection method: Spring-cage conn., Mounting: Soldering, Conductor/PCB connection direction: 90 °

The illustration shows the 10-position version

## Key commercial data

package_quantity	50
GTIN	4017918228743

## Technical data

### Dimensions

Length	12.6 mm
Pitch	2.54 mm
Dimension a	7.62 mm
Pin dimensions	0,5 x 0,8 mm
Hole diameter	1.1 mm

### General

Range of articles	FFKDS(A)/V
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	63 V
Rated voltage (III/2)	160 V
Rated voltage (II/2)	320 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	6 A
Nominal cross section	0.5 mm <sup>2</sup>
Solder pin surface	Sn
Stripping length	11 mm
Number of positions	4

### Connection data

Conductor cross section AWG/kcmil min.	26
Conductor cross section AWG/kcmil max	20

# PCB terminal block - FFKDSA1/V-2,54- 4 - 1789595

## Technical data

### Connection data

Minimum AWG according to UL/CUL	26
Maximum AWG according to UL/CUL	20

## classifications

### eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

### UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

## approvals

CSA / UL Recognized / cUL Recognized / cULus Recognized /

### Approval details


<b>Usegroups</b>	<b>B</b>
Nominal voltage UN	150 V
Nominal current IN	6 A
mm <sup>2</sup> /AWG/kcmil	20

--

# PCB terminal block - FFKDSA1/V-2,54- 4 - 1789595

## approvals

Usegroups	B
Nominal voltage UN	150 V
Nominal current IN	6 A
mm <sup>2</sup> /AWG/kcmil	26-20

cUL Recognized 	
Usegroups	B
Nominal voltage UN	150 V
Nominal current IN	6 A
mm <sup>2</sup> /AWG/kcmil	26-20

cULus Recognized 	
--	--

## Drawings

© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>