


# MA212 PCB Terminal Block, Modular



## DIMENSIONS/POSITIONS

## MA212-350M

間距	Pitch	3.50mm
位數	Poles	2 ~ 3Poles
尺寸a	Dimension a	3.50mm
長度 A	Length	A= 3.5xP(P≥2)
塑膠本體	Housing Material	PA 66
彈片	Spring	Stainless Strip Steel
端子	Contact	Brass, Tin Plated
螺紋	Screw Thread	M2.0, Steel, Zinc Plated
電線線徑	Wire Size	16 ~ 26AWG
PCB孔徑	PCB Hole Diameter	1.2mm
最大緊固扭矩	Tightening Torque, Max.	2.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I <sub>N</sub>	Nominal Current I <sub>N</sub>	6A
額定橫截面	Nominal Cross Section	-
最大負載電流	Maximum load current	6A
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94 Inflammability class acc. to UL94		V0
額定電壓, UL/CUL Nominal voltage, UL/CUL		300V
額定電流, UL/CUL Nominal current, UL/CUL		6A

