

SCHUKO socket outlet with die-cast cover



Model	
Cover version	solid plate
Design of the special power supply unit	without special current supply
Design of the socket / according to VDE 0620 for severe conditions	No
Design of the phase tap	No
General technical data	
Marking / of socket outlet	without imprint
Mounting type	fixing with claw and screw
Surface processing	others
Material	aluminum
Supply voltage	
Operating voltage / Rated value	230 V
Protection class	
Protection class IP	IP41
Main circuit	
Operating current / Rated value	16 A

Appearance

Color grey

Product details

Product component

- Ejection equipment No
- Labeling field No
- Increased touch protection No
- Fault current protection No
- miniature fuse No
- Integrated / functional lighting No
- Integrated / Light source No
- Integrated / orientation lighting No
- Hinged lid Yes

Product feature

- lockable No
- halogen-free Yes
- transparent No

Product function

Product function

- Socket selectable No
- Overvoltage protection No

Number

Number of units 1

Number of sockets / switchable 0

Connections

Arrangement of contacts / diagonal No

Type of electrical connection plug terminal

Mechanical Design

Height 95 mm

Width 95 mm

Depth 56 mm

Mounting type flush mounted

Material / of the enclosure metal

Certificates

Test Certificates

[Type Test Certificates/Test Report](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=5UB4650>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5UB4650>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5UB4650

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

