

**Industrial Ethernet  
IE-FM6C2UE0050MSD1SD0X**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Industrial Ethernet connection technology by Weidmüller offers the optimal solution for the infrastructure of your machine, system or factory. All connection technology is available from one source.

The benefits for you:

- IEC-standardised connectors, in the variants 1, 4, 5, 6 and 14
- Cat. 6 throughout<sub>A</sub> with **STEADYTEC**® technology
- pre-assembled cables and cables sold by the metre
- Copper and fibre-optic cables
- in IP20 and IP67
- all relevant industrial connections: RJ45, M12, SC, ...
- comprehensive range of accessories

**General ordering data**

|                 |   |
|-----------------|---|
| Available until | 2013-12-06  |
| Type            | IE-FM6C2UE0050MSD1SD0X  |
| Order No.       | <a href="#">1404410500</a>  |
| Version         | Dragline cable, SC IP 67 bayonet V01 metal, SC duplex IP 20, 62.5 µm, PUR, 50 m |
| GTIN (EAN)      | 4050118206661   |
| Qty.            | 1 pc(s).  |

**Industrial Ethernet  
IE-FM6C2UE0050MSD1SD0X**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Length     | 50 m    | Length (inches) | 1.969 inch |
| Net weight | 2,003 g |                 |            |

**Temperatures**

|                             |                |                             |                |
|-----------------------------|----------------|-----------------------------|----------------|
| Operating temperature, max. | 85 °C          | Operating temperature, min. | -40 °C         |
| Storage temperature, max.   | 85 °C          | Storage temperature, min.   | -55 °C         |
| Operating temperature       | -40 °C...85 °C | Storage temperature         | -55 °C...85 °C |
| Installation temperature    | -55 °C...60 °C |                             |                |

**Environmental Product Compliance**

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

**Fibre-optic**

|                           |   |                |  |
|---------------------------|---|----------------|--|
| Attenuation               | 2.7 dB/km at 850 nm, &le;<br>0.5 dB/km at 1300 nm | Bandwidth      | 200 MHz*km at 850 nm,<br>500 MHz*km at 1300 nm |
| Fibre type                | GOF, Multimode, OM1                               | Insertion loss | ≤ 0.4 dB                                       |
| Return loss (attenuation) | ≥ 30 dB   |                |  |

**Cable structure**

|                  |                    |                 |          |
|------------------|--------------------|-----------------|----------|
| Core diameter    | 62.5 µm            | Sheath diameter | 7.5–8 mm |
| Cable layout     | Break-out dragline | Material sheath | PUR      |
| Sheathing colour | black              |                 |          |

**Mechanical and material properties of cable**

|                                 |         |                                |       |
|---------------------------------|---------|--------------------------------|-------|
| Bending cycles                  | 100,000 | Min. bending radius, once only | 25 mm |
| Min. bending radius, repetitive | 70 mm   |                                |       |

**plug**

|                |                               |                 |                 |
|----------------|-------------------------------|-----------------|-----------------|
| Connector left | SC IP 67 bayonet V01<br>metal | Connector right | SC duplex IP 20 |
|----------------|-------------------------------|-----------------|-----------------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000034    | ETIM 6.0   | EC002599    |
| eClass 5.1 | 27-06-18-03 | eClass 6.2 | 27-06-18-03 |
| eClass 9.0 | 27-06-03-08 | eClass 9.1 | 27-06-03-08 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |   |
|--------------------|---|
| Brochure/Catalogue | <a href="#">FL FIELDWIRING EN</a><br><a href="#">PI PROFINET CABLING EN</a> |
| User Documentation | <a href="#">MAN IE GUIDE DE</a><br><a href="#">MAN IE GUIDE EN</a>          |