

**Industrial Ethernet  
IE-C5DS4VG0350A60A60-E**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**General ordering data**

Type	IE-C5DS4VG0350A60A60-E
Order No.	<a href="#">1522100350</a>
Version	System cable, RJ45 IP 20, RJ45 IP 20, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PVC, 35 m
GTIN (EAN)	4050118464269
Qty.	1 pc(s).

**Industrial Ethernet  
IE-C5DS4VG0350A60A60-E**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	35 m	Length (inches)	1.378 inch
Net weight	900 g	Insulation cross-section	1.5 mm

**Temperatures**

Operating temperature, max.	70 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	70 °C	Storage temperature, min.	-40 °C
Operating temperature	-40 °C...70 °C	Storage temperature	-40 °C...70 °C
Installation temperature	-20 °C...60 °C		

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**Electrical properties**

Insulation strength	500,000 Ω
---------------------	-----------

**Standards**

Standard, assembly	UL-Style 21694	Standard, insulating material	DIN EN 50290-2-23 (VDE 0819) Table 2/A (HD 624.3)
Standard, wire material	DIN EN 13602 Cu-ETP-A	Standard, shielding material	DIN EN 13602 Cu-ETP-A..B
Standard, additional standards	UL-File E11901 Vol.1 Sec.12 Page 1, UL-File E116441 Vol.1 Sec.6 Page 8		

**Cable structure**

Wire material	Stranded tin-plated copper wire	Standard designations	2YY(ST)CY 2x2x0.75/1,5-100 LI VZN GN
Strands	7	Cross-section	4*AWG 22/7 - 0.36 mm <sup>2</sup>
Insulation	PE	Insulation cross-section	1.5 mm
No. of wires	4	Arrangement of wire cores	Star-quad
Colour sequence or wires - wire pairs	white, yellow, blue, orange	Diameter of inner sheathing	3.9 mm
Filler	As central element	Shielding	SF/UTP
Complete shielding	Aluminium foil, Shielding braid made from copper wiring	Shielding braid thickness	0.13 mm
Overlap of shielding braid	85 %	Material sheath	PVC
Sheath diameter, min.	6.3 mm	Sheath diameter, max.	6.7 mm
Sheathing material thickness	0.9 mm	Sheathing colour	green (RAL 6018)

**Electrical properties of cable**

Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)	Operating voltage (UL rating)	600 V undefined
Test voltage: wire-wire-shield	2000 V <sub>eff</sub> , 50 Hz, 1 min	Characteristic impedance	100 ± 15 Ω at 1-100 MHz
Loop resistance	120 Ω/km	Transfer impedance	20 mΩ/m at 10 MHz
Insulation strength	500,000 Ω	Signal propagation time	5.3 ns/m

Creation date May 27, 2019 3:37:46 PM CEST

## Industrial Ethernet IE-C5DS4VG0350A60A60-E

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

# Technical data

### Mechanical and material properties of cable

Min. bending radius, once only	3.5 *diameter	Min. bending radius, repetitive	7.5 x cable diameter
Abrasion resistance	good	Resistance to spread of flame	in accordance with IEC 60332-1 / UL 1685

### plug

Connector left	RJ45 IP 20	Connector right	RJ45 IP 20
----------------	------------	-----------------	------------

### Classifications

ETIM 3.0	EC001262	ETIM 6.0	EC002599
UNSPSC	26-12-16-06	eClass 5.1	27-06-19-01
eClass 6.2	27-06-03-90	eClass 9.0	27-06-03-08
eClass 9.1	27-06-03-08		

### Approvals

ROHS	Conform
------	---------

### Downloads

Brochure/Catalogue	<a href="#">FL FIELDWIRING EN</a> <a href="#">PI PROFINET CABLING EN</a>
User Documentation	<a href="#">MAN IE GUIDE DE</a> <a href="#">MAN IE GUIDE EN</a>

**Data sheet****Industrial Ethernet  
IE-C5DS4VG0350A60A60-E**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings****Wiring**

---

RJ45		RJ45
1	yellow	1
2	orange	2
3	white	3
6	blue	6

---

---