



Illuminated pushbutton actuator, RMQ-Titan, Flush, momentary, yellow, Blank, Bezel: black



Powering Business Worldwide™



Part no. M22S-DL-Y
Catalog No. 216930
Alternate Catalog No. M22S-DL-YQ

Delivery program

Product range			RMQ-Titan
Basic function			Illuminated pushbutton actuators
Single unit/Complete unit			Single unit
Design			Flush momentary
Button plate			
button plate			yellow
Button plate			
			Blank
Degree of Protection			IP66, IP67, IP69
Front ring			Bezel: black
Connection to SmartWire-DT			yes with SWD-RMQ connections
Front dimensions			29,7

Technical data

General

Standards			IEC/EN 60947 VDE 0660
Lifespan, mechanical	Operations	x 10 ⁶	> 5
Operating frequency	Operations/h		≤ 3600
Actuating force	n		≤ 5
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Degree of Protection			IP66, IP67, IP69
Ambient temperature			
Open		°C	-25 - +70
Mounting position			As required
Mechanical shock resistance		g	30 Shock duration 11 ms Sinusoidal according to IEC 60068-2-27
shipping classification			DNV GL LR

Design verification as per IEC/EN 61439

Technical data for design verification				
Rated operational current for specified heat dissipation	I_n	A	0	
Heat dissipation per pole, current-dependent	P_{vid}	W	0	
Equipment heat dissipation, current-dependent	P_{vid}	W	0	
Static heat dissipation, non-current-dependent	P_{vs}	W	0	
Heat dissipation capacity	P_{diss}	W	0	
Operating ambient temperature min.		°C	-25	
Operating ambient temperature max.		°C	70	
IEC/EN 61439 design verification				
10.2 Strength of materials and parts				
10.2.2 Corrosion resistance				
			Meets the product standard's requirements.	
10.2.3.1 Verification of thermal stability of enclosures				
			Meets the product standard's requirements.	
10.2.3.2 Verification of resistance of insulating materials to normal heat				
			Meets the product standard's requirements.	
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects				
			Meets the product standard's requirements.	
10.2.4 Resistance to ultra-violet (UV) radiation				
			Please enquire	
10.2.5 Lifting				
			Does not apply, since the entire switchgear needs to be evaluated.	
10.2.6 Mechanical impact				
			Does not apply, since the entire switchgear needs to be evaluated.	
10.2.7 Inscriptions				
			Meets the product standard's requirements.	
10.3 Degree of protection of ASSEMBLIES				
			Does not apply, since the entire switchgear needs to be evaluated.	
10.4 Clearances and creepage distances				
			Meets the product standard's requirements.	
10.5 Protection against electric shock				
			Does not apply, since the entire switchgear needs to be evaluated.	
10.6 Incorporation of switching devices and components				
			Does not apply, since the entire switchgear needs to be evaluated.	
10.7 Internal electrical circuits and connections				
			Is the panel builder's responsibility.	
10.8 Connections for external conductors				
			Is the panel builder's responsibility.	
10.9 Insulation properties				
10.9.2 Power-frequency electric strength				
			Is the panel builder's responsibility.	
10.9.3 Impulse withstand voltage				
			Is the panel builder's responsibility.	
10.9.4 Testing of enclosures made of insulating material				
			Is the panel builder's responsibility.	
10.10 Temperature rise				
			Not applicable.	
10.11 Short-circuit rating				
			Is the panel builder's responsibility. The specifications for the switchgear must be observed.	
10.12 Electromagnetic compatibility				
			Is the panel builder's responsibility. The specifications for the switchgear must be observed.	
10.13 Mechanical function				
			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.	

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)				
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])				
Colour button				Yellow
Number of command positions				1
Construction type lens				Round
Hole diameter		mm		22,5
Width opening		mm		0
Height opening		mm		0
Type of button				Flat
Suitable for illumination				Yes
With protective cover				No
Labelled				No
Switching function latching				No
Spring-return				Yes
With front ring				Yes
Material front ring				Plastic
Colour front ring				Black

Degree of protection (IP), front side		IP67/IP69K
Degree of protection (NEMA), front side		4X

Approvals

Product Standards		IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.		E29184
UL Category Control No.		NKCR
CSA File No.		012528
CSA Class No.		3211-03
North America Certification		UL listed, CSA certified
Degree of Protection		UL/CSA Type 3R, 4X, 12, 13

Dimensions



Assets (links)

Declaration of CE Conformity

00003256