

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** SLV

**Supplier's address:** Axel Kranz, Daimlerstraße 21-23 52531 Übach-Palenberg Germany

**Model identifier:** 1005274

**Type of light source:**

|   |      |                                 |                            |
|---|------|---------------------------------|----------------------------|
| Lighting technology used:                           | LED  | Non-directional or directional: | DLS                        |
| Light source cap-type (or other electric interface) | GU10 |                                 |                            |
| Mains or non-mains:                                 | MLS  | Connected light source (CLS):   | No                         |
| Colour-tuneable light source:                       | No   | Envelope:                       | -                          |
| High luminance light source:                        | No   |                                 |                            |
| Anti-glare shield:                                  | No   | Dimmable:                       | Only with specific dimmers |

## Product parameters

| Parameter | Value | Parameter | Value |
|-----------|-------|-----------|-------|
|-----------|-------|-----------|-------|

### General product parameters:

|   |                          |  |                        |
|---|--------------------------|--|------------------------|
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer   | 8                        | Energy efficiency class  | F                      |
| Useful luminous flux ( $\phi_{\text{use}}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 680 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                  |
| On-mode power ( $P_{\text{on}}$ ), expressed in W   | 8,0                      | Standby power ( $P_{\text{sb}}$ ), expressed in W and rounded to the second decimal  | 0,00                   |
| Networked standby power ( $P_{\text{net}}$ ) for CLS, expressed in W and rounded to the second decimal  | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 90                     |
| Outer dimensions  | Height                   | Spectral power distribution in the   | See image in last page |
|   | Width                    |  |                        |

|   |       |       |  |                |
|---|-------|-------|--|----------------|
| without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)               | Depth | 111   | range 250 nm to 800 nm, at full-load                               |                |
| Claim of equivalent power <sup>(a)</sup>  |       | -     | If yes, equivalent power (W)                                       | -              |
|   |       |       | Chromaticity coordinates (x and y)                                 | 0,458<br>0,410 |
| <b>Parameters for directional light sources:</b>  |       |       |  |                |
| Peak luminous intensity (cd)  |       | 1 300 | Beam angle in degrees, or the range of beam angles that can be set | 38             |
| <b>Parameters for LED and OLED light sources:</b>   |       |       |  |                |
| R9 colour rendering index value   |       | 54    | Survival factor  | 1,00           |
| the lumen maintenance factor  |       | 0,70  |  |                |
| <b>Parameters for LED and OLED mains light sources:</b>   |       |       |  |                |
| displacement factor (cos $\phi_1$ )   |       | 0,99  | Colour consistency in McAdam ellipses                              | 6              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |       | -(b)  | If yes then replacement claim (W)                                  | -              |
| Flicker metric (Pst LM)   |       | 0,2   | Stroboscopic effect metric (SVM)                                   | 0,6            |

(a) '-': not applicable;

(b) '-': not applicable;

