## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLEGATED REGOL	-A11014 (L0) 2013/2	015 with regard to energ	gy labelling of light
Supplier's name	e or trade mark:	SLV		
Supplier's addre	ess: Christian Bar	nnert, Daimlerstraß	e 21-23 52531 Übach-Pa	lenberg Germany
Model identifie	r: 1005286			
Type of light so	urce:			
Lighting technol	logy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		<b>G</b> 9		
Mains or non-m	nains:	MLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance		No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para		
Parameter		Value	Parameter	Value
		General product p		T
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		4	Energy efficiency class	E
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), expressed in W		3,6	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	93
Outer	Height	54	Spectral power	See image
dimensions	Width	18	distribution in the	in last page
without	Depth	18		Page 1

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,430			
		coordinates (x and y)	0,400			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	57	Survival factor	0,00			
the lumen maintenance factor	0,90					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,89	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,0			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

