Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SLV

Supplier's address: Christian Bannert, Daimlerstraße 21-23 52531 Übach-Palenberg Germany

Model identifier: 1005303

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value		
General product parameters:						
0,	mption in on- 100 h), rounded st integer	8	Energy efficiency class	E		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode p expressed in W	oower (P _{on}),	7,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	93		
Outer	Height	105	Spectral power	See image		
dimensions	Width	60	distribution in the	in last page		
	L	1		Dage 1 / S		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	60	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,460 0,410		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	57	Survival factor	0,00		
the lumen main	tenance factor	0,93				
Parameters for	LED and OLED ma	ains light sources:				
displacement fa	ctor (cos φ1)	0,87	Colour consistency in McAdam ellipses	6		
source replaces	an LED light a fluorescent hout integrated icular wattage.	_(b)	lf yes then replacement claim (W)	-		
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-' : not applicable;

(b)'-' : not applicable;

