Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SLV

Supplier's address: Christian Bannert, Daimlerstraße 21-23 52531 Übach-Palenberg Germany

Model identifier: 1005304

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 00 h), rounded st integer	8	Energy efficiency class	F		
indicating if it rains in a sphere (30	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode p expressed in W	oower (P _{on}),	7,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90		
Outer	Height	105	Spectral power	See image		
dimensions	Width	60	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	60	range 250 nm to 800 nm, at full-load			
Claim of equival	lent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity coordinates (x and y)	0,460 0,410		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	53	Survival factor	1,00		
the lumen main	tenance factor	1,00				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,87	Colour consistency in McAdam ellipses	6		
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (P	Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-' : not applicable;

(b)'-' : not applicable;

