Product Information Sheet

Outer

dimensions

Height

Width

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	AHON (20) 2013/2	io 13 with regard to energ	gy labelling of light		
Supplier's name or trade mark:	SLV				
Supplier's address: Axel Kranz, Daimlerstraße 21-23 52531 Übach-Palenberg Germany					
Model identifier: 1005307					
Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Only with specific dimmers		
	Product para	meters			
Parameter	Value	Parameter	Value		
	General product p	T			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	14	Energy efficiency class	E		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 520 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W	13,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90		

140

45

Spectral

distribution in the

power

See image

in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	45	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-		
			Chromaticity	0,434		
			coordinates (x and y)	0,403		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	66	Survival factor	1,00		
the lumen maintenance factor		0,70				
Parameters for LED and OLED mains light sources:						
displacement fa	ctor (cos φ1)	0,96	Colour consistency in McAdam ellipses	6		
Claims that source replaces light source wit ballast of a parti	hout integrated	_(b)	If yes then replacement claim (W)	-		
Flicker metric (P	st LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)'-': not applicable; (b)'-': not applicable;

