Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	LLIGATED REGOL	-AITON (LO) 2013/2	015 with regard to energ	gy labelling of light		
Supplier's name	or trade mark:	SLV				
Supplier's address: Axel Kranz, Daimlerstraße 21-23 52531 Übach-Palenberg Germany						
Model identifier	: 1004708					
Type of light sou	irce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type		Unbekannt				
(or other electric interface) Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
		Product para	meters			
Parameter		Value	Parameter	Value		
		General product p		I		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		44	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode power (P _{on}), expressed in W		44,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90		
Outer	Height	2	Spectral power	See image		
dimensions	Width	10	distribution in the	in last page		
without	Depth	5 000		Page 1		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,457			
		coordinates (x and y)	0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	70	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

