## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: SLV

Supplier's address: Axel Kranz, Daimlerstraße 21-23 52531 Übach-Palenberg Germany

## Model identifier: 1004714

## Type of light source:

| Lighting technology used:     | LED       | Non-directional or directional: | NDLS |
|-------------------------------|-----------|---------------------------------|------|
| Light source cap-type         | Unbekannt |                                 |      |
| (or other electric interface) |           |                                 |      |
| Mains or non-mains:           | NMLS      | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No        | Envelope:                       | -    |
| High luminance light source:  | No        |                                 |      |
| Anti-glare shield:            | No        | Dimmable:                       | No   |

| Product parameters  |                                 |                           |   |              |  |  |  |
|---|---------------------------------|---------------------------|---|--------------|--|--|--|
| Parameter   |                                 | Value                     | Parameter   | Value        |  |  |  |
| General product parameters:   |                                 |                           |   |              |  |  |  |
| Energy consum<br>mode (kWh/100<br>up to the nearest                                       | 0 h), rounded                   | 73                        | Energy efficiency<br>class  | F            |  |  |  |
| Useful luminous<br>indicating if it ref<br>in a sphere (360<br>cone (120º) or in<br>(90º) | fers to the flux D°), in a wide | 7 000 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 4 000        |  |  |  |
| On-mode po<br>expressed in W  | ower (P <sub>on</sub> ),        | 73,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |  |
| Networked stand<br>for CLS, express<br>rounded to the se                                  | sed in W and                    | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 90           |  |  |  |
| Outer   | Height                          | 2                         | Spectral power  | See image    |  |  |  |
|   | Width                           | 10                        | distribution in the   | in last page |  |  |  |
| without   | Depth                           | 5 000                     | 1   | Page 1 /     |  |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |          | range 250 nm to 800<br>nm, at full-load |       |
|--|----------|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | -        | If yes, equivalent power (W)            | -     |
|  |          | Chromaticity                            | 0,381 |
|  |          | coordinates (x and y)                   | 0,379 |
| Parameters for LED and OLED light  | sources: |   |       |
| R9 colour rendering index value  | 85       | Survival factor                         | 1,00  |
| the lumen maintenance factor   | 0,96     |   |       |
| (a),   |          | I                                       |       |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

