## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			_			
Supplier's name	e or trade mark:	OSRAM				
Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany						
Model identifie	r: AC34139					
Type of light so	urce:					
Lighting techno	logy used:	other FL	Non-directional or directional:	NDLS		
Light source cap-type		G13				
(or other electric interface)						
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	d:	No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		62	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	8 800		
On-mode power (P <sub>on</sub> ), expressed in W		61,8	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	1 514	Spectral power	See image		
dimensions	Width	25	distribution in the	in last page		
without	Depth	25		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,294

(a)'-': not applicable; (b)'-': not applicable;

