Product Information Sheet

COMMISSION DELEGATED REGULATION (ELL) 2019/2015 with regard to energy labelling of light

sources	LATION (EU) 2019/20	015 with regard to ener	gy labelling of light			
Supplier's name or trade mark: OSRAM						
Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany Model identifier: AC34031						
						Type of light source:
Lighting technology used:	LFL_T5_HE	Non-directional or directional:	NDLS			
Light source cap-type	G5					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Yes			
Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded	21	Energy efficiency class	F			

Troduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
O ,	mption in on- 100 h), rounded st integer	21	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode pressed in W	oower (P _{on}),	20,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer dimensions without	Height	863	Spectral power	See image		
	Width	16	distribution in the	in last page		
	Depth	16				
				Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,380

(a)'-': not applicable; (b)'-': not applicable;

