## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| sources  | LLLOAILD KLOOI            | -A11014 (L0) 2013/2       | ots with regard to energ   | gy labelling of light |  |
|--|---------------------------|---------------------------|--|-----------------------|--|
| Supplier's name  | e or trade mark:          | OSRAM                     |  |                       |  |
| Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany  |                           |                           |  |                       |  |
| Model identifie  | er: AC34095               |                           |  |                       |  |
| Type of light so   | urce:                     |                           |  |                       |  |
| Lighting techno  | logy used:                | other FL                  | Non-directional or directional:  | NDLS                  |  |
| Light source cap-type  |                           | G13                       |  |                       |  |
| (or other electric interface)  |                           |                           |  |                       |  |
| Mains or non-m   | nains:                    | NMLS                      | Connected light source (CLS):  | No                    |  |
| Colour-tuneable  | e light source:           | No                        | Envelope:  | -                     |  |
| High luminance light source:   |                           | No                        |  |                       |  |
| Anti-glare shield  | d:                        | No                        | Dimmable:  | Yes                   |  |
| Product parameters   |                           |                           |  |                       |  |
| Parameter  |                           | Value                     | Parameter  | Value                 |  |
|  |                           | General product p         | T  |                       |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                           | 20                        | Energy efficiency class  | G                     |  |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                           | 1 250 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500                 |  |
| On-mode pexpressed in W  | oower (P <sub>on</sub> ), | 19,1                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00                  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                           | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                    |  |
| Outer  | Height                    | 604                       | Spectral power   | See image             |  |
| dimensions   | Width                     | 25                        | distribution in the  | in last page          |  |
| without  | Depth                     | 25                        |  | Page 1 / 3            |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|--|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)          | -     |
|  | Chromaticity coordinates (x and y)      | 0,313 |

(a)'-': not applicable; (b)'-': not applicable;

