Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Cuppliants assess		OCD A N /		
	e or trade mark:			
Supplier's addr	ess: LEDVANCE G	mbH, Parkring 33, 0	Garching, Germany	
Model identifie	er: AC34216			
Type of light so	urce:			
Lighting techno	logy used:	CFLni	Non-directional or directional:	NDLS
Light source cap	o-type	G24q-1		
(or other electric interface)				
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance		No		
Anti-glare shield:		No	Dimmable:	Yes
		Product para	T	I
Parameter		Value	Parameter	Value
		General product	T	_
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		11	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		10,7	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions	Height	103	Spectral power	See image
	Width	12	distribution in the	in last page
without	Depth	12		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,380

(a)'-': not applicable; (b)'-': not applicable;

