## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

or trade mark: ss: LEDVANCE G : AC34273			
	mbH, Parkring 33, (		
: AC34273		Garching, Germany	
rce:			
gy used:	CFLni	Non-directional or directional:	NDLS
type	2G7		
interface)			
ins:	NMLS	Connected light source (CLS):	No
light source:	No	Envelope:	-
	No		
	No	Dimmable:	Yes
-	<u>-</u>	T	Γ -
	Value	Parameter	Value
		T	T
0 h), rounded	9	Energy efficiency class	G
fers to the flux 0º), in a wide a narrow cone	600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
ower (P <sub>on</sub> ),	8,7	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
sed in W and	<u>-</u>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
	151	Spectral power	See image
Width	12	distribution in the	in last page
	ption in on- 0 h), rounded tinteger s flux (фuse), fers to the flux 0º), in a wide a narrow cone  by power (Pon), by power (Pon), the property of the property	interface) ins: NMLS  light source: No ight source: No Product para Value  General product p  ption in on- 0 h), rounded tinteger s flux (фuse), fers to the flux 0°), in a wide a narrow cone  ower (Pon), by power (Pnet) sed in W and econd decimal  Height Height 151 Width 12	interface)  No  Envelope:  ight source:  No  No  Dimmable:  Product parameters  Value  Parameter  General product parameters:  ption in on- 0 h), rounded integer  integer

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,440

(a)'-': not applicable; (b)'-': not applicable;

