Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | DELLOATED REGOT | -AITON (LO) 2013/2 | ots with regard to energ | gy labelling of light |
|--|---------------------------|---------------------------|--|-----------------------|
| Supplier's nam | e or trade mark: | OSRAM | | |
| Supplier's addr | ess: LEDVANCE G | imbH, Parkring 33, 0 | Garching, Germany | |
| Model identifie | er: AC34292 | | | |
| Type of light so | ource: | | | |
| Lighting techno | logy used: | CFLni | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | | 2G11 | | |
| Mains or non-n | nains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneabl | e light source: | No | Envelope: | - |
| High luminance light source: | | No | | |
| Anti-glare shiel | d: | No | Dimmable: | Yes |
| | | Product para | meters | |
| Parameter | | Value | Parameter | Value |
| | | General product p | parameters: | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 58 | Energy efficiency class | G |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 4 320 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode expressed in W | power (P _{on}), | 55,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer | Height | 538 | Spectral power | See image |
| dimensions | Width | 17 | distribution in the | in last page |
| without | Depth | 17 | | Page 1 / |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,380 |

(a)'-': not applicable; (b)'-': not applicable;

