Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: OSRAM

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC34176

Type of light source:

| Lighting technology used: | other FL | Non-directional or directional: | NDLS | | |
|-------------------------------|----------|---------------------------------|------|--|--|
| Light source cap-type | 2GX13 | | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | No | Envelope: | - | | |
| High luminance light source: | No | | | | |
| Anti-glare shield: | No | Dimmable: | Yes | | |
| Product parameters | | | | | |

| Parameter | | Value | Parameter | Value | | |
|-----------------------------------------------------|--------------------------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|--|
| General product parameters: | | | | | | |
| Energy consum mode (kWh/10 up to the neares | 00 h), rounded | 24 | Energy efficiency class | G | | |
| | • | 1 900 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 | | |
| On-mode p expressed in W | ower (P _{on}), | 23,8 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked stan for CLS, expres rounded to the | sed in W and | _ | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer | Height | 240 | Spectral power | See image | | |
| dimensions without | Width | 16 | distribution in the | in last page | | |
| | Depth | 16 | 1 | Page 1 / | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,380 |

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

