Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name | e or trade mark: | OSRAM | | |
|--|------------------|---------------------------|--|---------------------------|
| | | | Carabia Caraba | |
| | | mbH, Parkring 33, (| Garching, Germany | |
| Model identifie | r: AC34306 | | | |
| Type of light so | urce: | | | |
| Lighting technol | logy used: | CFLni | Non-directional or directional: | NDLS |
| Light source cap-type | | GR8 | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | | No | Envelope: | - |
| High luminance | | No | | |
| Anti-glare shield: | | No | Dimmable: | No |
| | | Product para | | |
| Parameter | | Value | Parameter | Value |
| _ | | General product p | 1 | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 17 | Energy efficiency class | G |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 1 050 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode power (P _{on}), expressed in W | | 16,7 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| | | | | |
| Outer dimensions | Height Width | 136 141 | Spectral power distribution in the | See image in last page |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,463 |

(a)'-': not applicable; (b)'-': not applicable;

