Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LEDVANCE

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC35335

Type of light source:

Lighting technology used:	other	Non-directional or directional:	NDLS	
Light source cap-type	R7s			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				

Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer1 580Energy classUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)33 730 in Sphere (360°)Correlate temperat rounded nearest or the correlated temperat rounded nearest 1 can be seOn-mode expressed in W01 580,0Standby p expressed in W and rounded to the second decimalNetworked standby power (Pnet) for CLS, expressed in W-Colour index, ro the nearest or the radius or the radius	er	Value			
mode(kWh/1000 h), rounded up to the nearest integerClassUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)33 730 in Sphere (360°)Correlate temperat rounded nearest or the correlated temperat rounded nearest 1 can be seOn-mode powerpower (Pon), expressed in W1 580,0Standby power expressed in W and rounded to the second decimalNetworked standby power (Pnet) rounded to the second decimal-Colour index, ro the neare or the rai values the	General product parameters:				
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (P _{on}), expressed in W Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	efficiency	G			
expressed in W expressed expressed in W expressed and roun second de Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal or the neare or the ran values the	ture, to the 100 K, range of d colour tures, to the 100 K, that	3 000			
for CLS, expressed in W and rounded to the second decimal or the rear values th	nded to the	0,00			
	rendering ounded to rest integer, inge of CRI- hat can be	100			
Outer Height 256 Spectral	power	See image			
	on in the	in last page			
without Depth 12					

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,444

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

