Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources | LLEGATED REGOT | AHON (LO) 2013/2 | 015 with regard to energ | gy labelling of light |
|--|------------------|----------------------------|--|-----------------------|
| Supplier's name | e or trade mark: | LEDVANCE | | |
| Supplier's addre | ess: LEDVANCE G | mbH, Parkring 33, 0 | Garching, Germany | |
| Model identifie | r: AC35337 | | | |
| Type of light so | urce: | | | |
| Lighting technol | logy used: | other | Non-directional or directional: | NDLS |
| Light source cap-type | | R7s | | |
| (or other electric interface) | | | | |
| Mains or non-m | nains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable | e light source: | No | Envelope: | - |
| High luminance light source: | | No | | |
| Anti-glare shield: | | No | Dimmable: | Yes |
| | | Product para | | |
| Parameter | | Value | Parameter | Value |
| | | General product p | | _ |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 2 031 | Energy efficiency class | G |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 43 470 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 900 |
| On-mode power (P _{on}), expressed in W | | 2 030,0 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 100 |
| Outer | Height | 333 | Spectral power | See image |
| dimensions | Width | 12 | distribution in the | in last page |
| without | Depth | 12 | | Page 1 |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|--------------------------------------|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,444 |

(a)'-': not applicable; (b)'-': not applicable;

