Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DIGITUS	

Supplier's address:	Product Management,	Auf dem Schüffel 3	, 58513 Lüdenscheid,	DE

Model identifier:	DN-19 LIGHT-3
-------------------	---------------

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	NA		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

		1 Todact para		
Parameter		Value	Parameter	Value
		General product p	parameters:	
_ ·	mption in on- 100 h), rounded est integer	3	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), refers to the flux .60º), in a wide in a narrow cone	300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode properties of the contract of the cont	power (P _{on}),	3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer	Height	300	Spectral power	See image
dimensions	Width	28	distribution in the	in last page
				Page 1 / 3

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	9	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,315
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	3	Survival factor	1,00
the lumen main	tenance factor	0,95		

(a)'-': not applicable;

(b)'-': not applicable;

