Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: MEGAMAN

Supplier's address: IDV GmbH MEGAMAN-Confirmation-Management, Birkenweiherstraße 2, 63505 Langenselbold, DE

Model identifier: MM49162-2

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | | |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type | G4 | | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | Nein | | | |
| Colour-tuneable light source: | Nein | Envelope: | - | | | |
| High luminance light source: | Nein | | | | | |
| Anti-glare shield: | Nein | Dimmable: | No | | | |
| Product parameters | | | | | | |

| Parameter | Value | Parameter | Value | | | |
|---|---------------|---|--------------|--|--|--|
| General product parameters: | | | | | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | Energy efficiency class | G | | | |
| Useful luminous flux (duse), indicating if it refers to the flux in a sphere (360 [°]), in a wide cone (120 [°]) or in a narrow cone (90 [°]) | Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | | | |
| On-mode power (P _{on}), expressed in W | 1,2 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | | |
| Outer Height | 32 | Spectral power | See image | | | |
| dimensions Width | 10 | distribution in the | in last page | | | |

| without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | Depth | 10 | range 250 nm to 800 nm, at full-load | | | |
|---|--------------------------|------|---|-------|--|--|
| Claim of equival | ent power ^(a) | - | lf yes, equivalent power (W) | - | | |
| | | | Chromaticity | 0,458 | | |
| | | | coordinates (x and y) | 0,412 | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rende | ring index value | 0 | Survival factor | 0,90 | | |
| the lumen maint | tenance factor | 0,90 | | | | |
| (a) | | | | | | |

(a)'-' : not applicable;

(b)'-' : not applicable;

