Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or	trade mark:	MEGAMAN
--------------------	-------------	---------

Supplier's address: IDV GmbH MEGAMAN-Confirmation-Management, Birkenweiherstraße 2,

63505 Langenselbold, DE

Mode	l identifier:	MM21093
------	---------------	---------

IVI	~~		anı	,	111 1	\boldsymbol{c}
IVL			211		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Typ		,	о			•••

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	No

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
	nption in on- 00 h), rounded st integer	7	Energy efficiency class	F
indicating if it re in a sphere (3)	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 800
On-mode pexpressed in W	oower (P _{on}),	7,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	_
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	101	Spectral power	See image
dimensions	Width	40	distribution in the	in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	40	range 250 nm to 800 nm, at full-load		
Claim of equivale	ent power ^(a)	Ja	If yes, equivalent power (W)	48	
			Chromaticity coordinates (x and y)		
Parameters for L	ED and OLED lig	ht sources:			
R9 colour render	ing index value	-	Survival factor	0,50	
the lumen maintenance factor		0,70			
Parameters for LED and OLED mains light sources:					
displacement fac	tor (cos φ1)	-	Colour consistency in McAdam ellipses	6	
Claims that a source replaces light source with ballast of a partic	out integrated	_(b)	If yes then replacement claim (W)	-	
Flicker metric (Ps	t LM)	-	Stroboscopic effect metric (SVM)	-	

(a)'-': not applicable; (b)'-': not applicable;