Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Gnosjö Konstsmide AB

Supplier's address: -

Model identifier: 6320-810

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS | | | |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type | - | | | | | |
| (or other electric interface) | | | | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | Nein | | | |
| Colour-tuneable light source: | Nein | Envelope: | - | | | |
| High luminance light source: | Nein | | | | | |
| Anti-glare shield: | Nein | Dimmable: | No | | | |
| Product parameters | | | | | | |

| | | | lieters | | | |
|---|--|----------|---|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consum mode (kWh/10 up to the neares | 00 h), rounded | 6 | Energy efficiency class | F | | |
| indicating if it re in a sphere (36 | us flux (фuse), efers to the flux 50º), in a wide n a narrow cone | 100 in - | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | _ | | |
| On-mode p expressed in W | oower (P _{on}), | 4,8 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,30 | | |
| Networked stan for CLS, expres rounded to the | | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | | | |
| Outer | Height | - | Spectral power | See image | | |
| dimensions | Width | - | distribution in the | in last page | | |
| without | Depth | - | 1 | Soito 1 / 2 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | | |
|--|------|--|---|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordinates (x and y) | | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | - | Survival factor | - | | | |
| the lumen maintenance factor | - | | | | | |
| Parameters for LED and OLED mains light sources: | | | | | | |
| displacement factor (cos φ1) | - | Colour consistency in McAdam ellipses | - | | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W) | - | | | |
| Flicker metric (Pst LM) | - | Stroboscopic effect metric (SVM) | - | | | |

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;