Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: as - Schwabe

Supplier's address: -

Model identifier: 46323

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS		
Light source cap-type	SMD				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	No		
Product parameters					

		Fibluct para			
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consum mode (kWh/10 up to the neares	00 h), rounded	10	Energy efficiency class	E	
indicating if it re	us flux (фuse), efers to the flux 50º), in a wide n a narrow cone	1 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode p expressed in W	ower (P _{on}),	10,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80	
Outer	Height	-	Spectral power	See image	
dimensions	Width	-	distribution in the	in last page	
without	Depth	-			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load					
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-				
	Chromaticity coordinates (x and y)	-				
Parameters for directional light sources:						
Peak luminous intensity (cd)	- Beam angle in degrees, or the range of beam angles that can be set					
Parameters for LED and OLED light sources:						
R9 colour rendering index value	- Survival factor	-				
the lumen maintenance factor	-					
(a)						

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;