## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: as - Schwabe  |               |                              |  |              |  |  |  |
|--|---------------|------------------------------|--|--------------|--|--|--|
| Supplier's address: -  |               |                              |  |              |  |  |  |
| Model identifie  | r: 46324      |                              |  |              |  |  |  |
| Type of light so   | urce:         |                              |  |              |  |  |  |
| Lighting techno  | logy used:    | LED                          | Non-directional or directional:  | DLS          |  |  |  |
| Light source cap-type  |               | SMD                          |  |              |  |  |  |
| (or other electri  | ic interface) |                              |  |              |  |  |  |
| Mains or non-mains:  |               | NMLS                         | Connected light source (CLS):  | Nein         |  |  |  |
| Colour-tuneable light source:  |               | Nein                         | Envelope:  | -            |  |  |  |
| High luminance light source:   |               | Nein                         |  |              |  |  |  |
| Anti-glare shield:   |               | Nein                         | Dimmable:  | -            |  |  |  |
| Product parameters   |               |                              |  |              |  |  |  |
| Parameter  |               | Value                        | Parameter  | Value        |  |  |  |
| General product parameters:  |               |                              |  |              |  |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |               | 20                           | Energy efficiency class  | F            |  |  |  |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |               | 1 800 in Wide<br>cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |  |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |               | 20,0                         | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |               | -                            | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |  |  |  |
| Outer  | Height        | -                            | Spectral power   | See image    |  |  |  |
| dimensions   | Width         | -                            | distribution in the  | in last page |  |  |  |
| without  | Depth         | -                            |  |              |  |  |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) |   | range 250 nm to 800<br>nm, at full-load                            |   |  |  |  |
|--|---|--|---|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | - | If yes, equivalent power (W)                                       | - |  |  |  |
|  |   | Chromaticity coordinates (x and y)                                 | - |  |  |  |
| Parameters for directional light sources:  |   |  |   |  |  |  |
| Peak luminous intensity (cd)   | - | Beam angle in degrees, or the range of beam angles that can be set |   |  |  |  |
| Parameters for LED and OLED light sources:   |   |  |   |  |  |  |
| R9 colour rendering index value  | - | Survival factor  | - |  |  |  |
| the lumen maintenance factor   | - |  |   |  |  |  |

(a)'-': not applicable; (b)'-': not applicable;