Product Information Sheet

Height

Width

Depth

Outer

without

dimensions

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier 3 hame of Gade mark. Triber 3 |
|---|
| Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL |
| |

| sources | | | |
|--|-------------------------|--|----------------------|
| Supplier's name or trade mark: | PHILIPS | | |
| Supplier's address: Customer Ca | are Philips, I.B.R.S./0 | C.C.R.I. /Numéro 10461, | 5600VB Eindhoven, NL |
| Model identifier: 9290020285 | | | |
| Type of light source: | | | |
| Lighting technology used: | LED | Non-directional or directional: | NDLS |
| Light source cap-type | E14 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |
| | Product para | meters | |
| Parameter | Value | Parameter | Value |
| | General product p | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | 7 | Energy efficiency class | Е |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 806 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode power (P _{on}), expressed in W | 6,5 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |

80

45

45

Spectral

distribution in the

power

| D | 4 | - / | 2 |
|------|-----|-----|---|
| Page | - 1 | / | 3 |
| | | | |

See image

in last page

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | | | |
|---|------|---|-------|--|--|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 60 | | |
| | | Chromaticity coordinates (x and y) | 0,458 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | 1 | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,93 | | | | |
| Parameters for LED and OLED m | | | | | |
| displacement factor (cos φ1) | 0,50 | Colour consistency in McAdam ellipses | 6 | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replacement claim (W) | - | | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,9 | | |

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

