Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

ų	
	Supplier's name or trade mark: PHILIPS

Supplier's address:	Customer Care Philip	os, I.B.R.S./C.C.R.I. /Numér	o 10461, 5600VB Eindhoven	, NL
---------------------	----------------------	------------------------------	---------------------------	------

Model identifier:	9290012429D
-------------------	-------------

Tyne	of light sou	ırca.
IVDE	OI HEHL SOL	JILE.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
<u> </u>	mption in on- 100 h), rounded st integer	5	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide n a narrow cone	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pressed in W	oower (P _{on}),	4,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	106	Spectral power distribution in the	See image
dimensions	Width	60		in last page
without	Depth	60		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	40		
		Chromaticity coordinates (x and y)	0,458		
Parameters for LED and OLED lig	ht sources:				
R9 colour rendering index value	1	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED m	Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,51	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

