Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL
Model identifier: 9290020551

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	G9				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter Value Parameter Value **General product parameters:** 5 Energy consumption in on-Energy efficiency Ε mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (фuse), 570 in Correlated colour 2 700 indicating if it refers to the flux Sphere (360°) temperature, in a sphere (360º), in a wide rounded to the cone (120º) or in a narrow cone nearest 100 Κ, (90°) or the range of correlated colour temperatures,

			rounded to the nearest 100 K, that can be set	
On-mode expressed in W	power (P _{on}), /	4,8	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	ndby power (P _{net}) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	60	Spectral power	See image
dimensions	Width	19	distribution in the	in last page
without	Depth	19		
•			·	Page 1 /

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60		
		Chromaticity coordinates (x and y)	0,458		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,40	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

