Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Jakob Maul GmbH, Jakob-Maul-Str. 17 D-64732 Bad König

Model identifier: 8200609.200

_	•			
Type	Λt	light	COLL	rca.
IVDE	VI.	HEILL	SOU	LC.

Type of light source:					
Lighting technol	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap	Light source cap-type				
(or other electric interface)		Anschlussklemmen			
Mains or non-mains:		NMLS	Connected light	No	
Colour tupophic light course.		No	source (CLS): Envelope:		
	Colour-tuneable light source:		Lilvelope.	-	
Anti-glare shield	High luminance light source:		Dimmable:	Yes	
Anti-giare silier	Anti-glare shield: No Dimmable: Yes Product parameters				
Parameter		Value	Parameter	Value	
Tarameter		General product pa		value	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	5	Energy efficiency class	D	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		769 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode prespressed in W	oower (P _{on}),	5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81	
Outer	Height	78	Spectral power	See image	
dimensions	Width	78	distribution in the	in last page	
without	Depth	5			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	58			
		Chromaticity	0,434			
		coordinates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-1	Survival factor	1,00			
the lumen maintenance factor	0,94					

(a)'-': not applicable; (b)'-': not applicable;

