Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	MAUL		
Supplier's address: Jakob Maul	GmbH, Jakob-Maul-S	tr. 17 D-64732 Bad Kön	ig
Model identifier: 8205809.200			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Kabel		
(or other electric interface)	Anschlussklemmen, cable connector		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product paran	neters	
Parameter	Value	Parameter	Value
	General product pa	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	11	Energy efficiency class	E
Useful luminous flux (фuse),	1 449 in	Correlated colour	6 500

General product parameters.						
	mption in on- 100 h), rounded st integer	11	Energy efficiency class	Е		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 449 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode pressed in W	power (P _{on}),	10,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81		
Outer	Height	310	Spectral power	See image		
dimensions	Width	42	distribution in the	in last page		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	5	range 250 nm to 800 nm, at full-load			
Claim of equival	ent power ^(a)	Yes	If yes, equivalent power (W)	96		
			Chromaticity	0,312		
			coordinates (x and y)	0,328		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	-2	Survival factor	1,00		
the lumen main	tenance factor	0,95				

(a)'-': not applicable;

(b)_{'-'} : not applicable;

