Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier	's n	ıame	or	trade	mark:	MAUL	
----------	------	------	----	-------	-------	------	--

Supplier's address: Jakob Maul GmbH, Jakob-Maul-Str. 17 D-64732 Bad König

Model identifier: 8180109.200

Type of light sour	Type	of li	ght	sourc	e:
--------------------	------	-------	-----	-------	----

without

Depth

776 - 1.00						
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap	Light source cap-type					
(or other electric interface)		Anschlussklemmen				
Mains or non-m	ains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable	light source:	No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	l:	No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
		General product p	arameters:			
<u> </u>	nption in on- 00 h), rounded st integer	3	Energy efficiency class	G		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		224 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30005700		
On-mode power (P _{on}), expressed in W		2,9	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82		
Outer	Height	106	Spectral power	See image		
dimensions	Width	33	distribution in the	in last page		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	23			
		Chromaticity	0,434			
		coordinates (x and y)	0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	6	Survival factor	1,00			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;

