Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LEDVANCE

Supplier's address: LEDVANCE GmbH, Parkring 33, Garching, Germany

Model identifier: AC32327

Type of light source:

Colour-tuneable light source:	No	Envelope:	-
Colour-tuneable light source:	No	Envelope:	-
	IVILS	source (CLS):	ÎNU
Mains or non-mains:	MLS	Connected light	No
(or other electric interface)			
Light source cap-type	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Deveneeter		Value		Malua			
Parameter		Value	Parameter	Value			
General product parameters:							
0,	mption in on- 000 h), rounded est integer	3	Energy efficiency class	E			
indicating if it in a sphere (3	pus flux (φuse), refers to the flux 360º), in a wide in a narrow cone	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700			
On-mode expressed in W	power (P _{on}),	2,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
for CLS, expre	ndby power (P _{net}) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80			
Outer dimensions without	Height	105	Spectral power	See image			
	Width	60	distribution in the	in last page			
	Depth	60					
			I	Page 1			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	25				
		Chromaticity coordinates (x and y)	0,463				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	0	Survival factor	0,90				
the lumen maintenance factor	0,70						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,40	Colour consistency in McAdam ellipses	6				
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-				
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9				

(a)'-' : not applicable;

(b)'_-' : not applicable;

