Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS	
---	--

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIKIIL	source.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value
General product parameters:				
0,	mption in on- 100 h), rounded st integer	8	Energy efficiency class	F
indicating if it re in a sphere (3)	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	650 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pexpressed in W	oower (P _{on}),	7,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	180	Spectral power	See image
dimensions	Width	125	distribution in the	in last page

without Separate control gear, lighting control parts and non-lighting control parts,	125	range 250 nm to 800 nm, at full-load	
if any (millimetre)			
Claim of equivalent power	a) Yes	If yes, equivalent power (W)	50
		Chromaticity coordinates (x and y)	0,458
Parameters for LED and OI	.ED light sources:		
R9 colour rendering index	value 1	Survival factor	0,90
the lumen maintenance fac	ctor 0,93		
Parameters for LED and OI	ED mains light sources:	-	
displacement factor (cos φ	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED source replaces a fluores light source without integral ballast of a particular watta	ated	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)'-': not applicable; (b)'-': not applicable;

