Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 9290024443

Type of light source:

Light source cap-type (or other electric interface)	S14S		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consump mode (kWh/1000 up to the nearest) h), rounded	4	Energy efficiency class	F		
Useful luminous indicating if it refe in a sphere (360 cone (120 ^o) or in a (90 ^o)	ers to the flux P), in a wide	375 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode pov expressed in W	wer (P _{on}),	3,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stands for CLS, expresse rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer H	Height	500	Spectral power	See image		
dimensions	Width	30	distribution in the	in last page		
without [Depth	30	-			
1	-	1	1	Page 1 /		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,458			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,75	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)'-' : not applicable;

(b)'_-' : not applicable;

