## **Product Information Sheet**

for CLS, expressed in W and

rounded to the second decimal

Height

Width

Depth

Outer

without

dimensions

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			
Supplier's name or trade mark:	PHILIPS		
Supplier's address: Customer Ca	re Philips, I.B.R.S./0	C.C.R.I. /Numéro 10461,	5600VB Eindhoven, NL
Model identifier: 9290019490			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E14		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	E
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)  On-mode power (P <sub>on</sub> ),	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	0,00
expressed in W	۷,1	expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> )	-	Colour rendering	80

index, rounded to

the nearest integer, or the range of CRIvalues that can be

distribution in the

power

set

Spectral

90

25

25

Page	1	/ 3	

See image

in last page

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	25				
		Chromaticity coordinates (x and y)	0,458				
Parameters for LED and OLED	ght sources:						
R9 colour rendering index value	1	Survival factor	0,90				
the lumen maintenance factor	0,93						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,51	Colour consistency in McAdam ellipses	6				
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	:	If yes then replacement claim (W)	-				
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4				

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

